


**V-TAG 36** 



# GENERAL SPECIFICATIONS

- Frequency: 13.56 MHz
- IC: NXP NTAG 213 TT NFC T2T compliant IC. Alternative ICs: NXP NTAG 424 DNA, SIC SIC43NT
- Protocols: ISO/IEC 14443-A, 15693 compliance, and NFC Forum Type 2 Tag
- Substrate: Paper (e.g., wood-free cast-coated white high-gloss on one side, 100% PEFC certified) and PET. Alternative substrates are available upon request
- Product available as wet inlay, wet white, or antenna only



#### **APPLICATIONS**

E-commerce of FMCG

Customer engagement

Web
authentication
& anticounterfeiting

Secured documents

Sensor applications

## **PRODUCT CHARACTERISTICS**

- Antenna material: Conductive silver ink
- Finishing options: Dry inlays, wet inlays to your specific adhesive requirements upon request
- Customization upon request
- Final inspection: 100% tested, faulty tags

### **RFID CHIP SILICON**

Operating frequency: 13.56 MHz

Operating temperature range: 25 °C up to +70 °C

Read sensitivity: -21 dBm Write sensitivity: -16 dBm\*

Automatic NFC counter triggered at read command AES-128 crypto for NFC web based authentication

\* data based on NXP NTAG213TT


## **MECHANICAL DIMENSION**

Antenna Size: 36 mm / 1.42 inch (ø, diameter) Label Size: 40 x 40 mm / 1.57 x 1.57 inch

#### LIFECYCLE MANAGEMENT

100% recyclable with 75% - 95% of material components that can be recovered (paper-based version)

ISO 59040 Product Circularity Datasheet (PCDS) available upon request for more information



**JOANEO BY VICTOR BUCK SERVICES** 



IVY Building, 13-15, Parc d'Activités L-8308 Capellen Luxembourg

> Rue de l'Industrie, L-3895 Mondercange Luxembourg



(+352) 49 98 66 1



contact@joaneo.com



www.joaneo.com



